

ビーム放射分光のヘリオトロンJ密度変調実験への適用

**Application of beam emission spectroscopy
to density modulation experiments in Heliotron J**

小林進二¹, 永榮蓉子², 門信一郎³, 大石鉄太郎⁴, 山本聡¹, 長崎百伸¹, 大島慎介¹, 田中謙治⁴,
水内亨¹, 岡田浩之¹, 南貴司¹, Lee Hyunyoung¹, 永岡賢一⁴, 鈴木康浩⁴, 渡邊清政⁴, 村上定義⁵,
中嶋洋輔⁶, 中村祐司², 木島滋¹, 向井清史⁴, 東使潔¹, 佐野史道¹
KOBAYASHI Shinji¹, NAGAE Yoko², KADO Shinichiro³, OISHI Tetsutarou⁴, et al.

¹京大エネ理工研, ²京大エネ科, ³東大院工, ⁴核融合研, ⁵京大院工, ⁶筑波大プラセ
¹IAE, Kyoto Univ., ²GSES, Kyoto Univ., ³Sch. Eng., Univ. Tokyo, ⁴NIFS, ⁵Grad. Sch. Eng, Kyoto Univ., ⁶PRC
Tsukuba Univ.

Beam emission spectroscopy (BES) provides the experimental information of the density fluctuation at a local region where the sightline intersects the path of the neutral beam (NB). When we apply the BES diagnostic to the density modulation experiments, the beam integration effect due to the beam absorption should be taken into account in the case of the analysis on the modulation amplitude and its phase.

Recently, we have installed the BES diagnostic to the Heliotron J device, having a helical-axis magnetic configuration [1]. The radial profiles of the density fluctuation due to the fast-ion driven MHD activities have been measured. In this study, we investigate the response of the BES intensity to the density modulation to discuss the applicability of the BES diagnostics to the transport analysis.

Figure 1 shows the temporal evolutions of plasma parameters obtained in the density modulation experiments. The plasma was heated by ECH+NBI. The gas puffing was changed with the




Fig. 1. Time evolution of the heating, gas fueling, density, stored energy and BES intensity obtained in the density modulation experiments.

modulation frequency of 50 Hz. The line-averaged electron density was $\bar{n}_e = 8.7 \times 10^{18} \text{ m}^{-3}$ and the modulation amplitude was $\Delta \bar{n}_e = \pm 5.4 \times 10^{17} \text{ m}^{-3}$ (i.e. $\Delta \bar{n}_e / \bar{n}_e \sim \pm 0.06$). A modulation of the BES intensity was observed.

We applied the fast Fourier transform analysis to evaluate the modulation amplitude and its phase. Figure 2 shows the radial profile of the modulation amplitude normalized by the mean value of the BES intensity and the phase difference to the gas puffing signal. The BES modulation amplitude at the core region ($\Delta I_{BE} / I_{BE} \sim \pm 0.025$) was about the half of the modulation amplitude for the line averaged density. To know the absolute value of the modulation amplitude, the radial profile of the density is required. As compared with the phase obtained by the microwave reflectometer in the previous density modulation experiments, the change in the phase difference at $r/a > 0.5$ was much larger than that by the reflectometer [2], which may be due to the beam integration effect. We will investigate the sensitivity of the density modulation to the BES intensity using a numerical calculation including the beam absorption calculation.

[1] S. Kobayashi, et al., RSI **83** 10D535 (2012).

[2] 向井, 他 第 27 回年会 02P50 (2010).




Fig. 2. Radial profile of the normalized modulation amplitude and phase difference to gas fueling.